

Product Technical Data Sheet MANUFACTURER: AG Termopasty Grzegorz Gąsowski ul. Kolejowa 33 E. 18-218 Sokoły, phone 86 274 13 42

ul. Kolejowa 33 E, 18-218 Sokoły, phone 86 274 13 42

Graphite varnish

Product intended for the repair of graphite-coated boards, e.g., in remote controls and calculators. Suitable also for restoring bridge function and the repair of interrupted paths. The set contains two vials (graphite varnish and a solvent).

Application:

- provision of graphite coating losses in printed circuit boards,
- securing silver-plated contacts against harmful direct contact between silver and rubber (e.g., in remo-
- formation or reconstruction of paths in (low-current) printed circuit boards.

Physicochemical properties:

Parameters	UoM	Result
Density	g/cm³	0,97
Viscosity	Pa∙s	80-100

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
2 x 1,5 ml	vial	5	ART.AGT-022

Warehousing:

Store in dry and well-ventilated areas away from sources of heat and ignition and direct sunlight.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.

